



The Scientific Temper

JULY 2026 Vol. 17 (7): 6580-6598

ISSN: 0976-8653, E-ISSN: 2231-6396

DOI: 10.58414/SCIENTIFICTEMPER.2026.17.7.2497

<https://scientifictemper.com/>

RESEARCH ARTICLE

Analysis of an M/M/1 Working Vacation Queue with Reactive State-Dependent Customer Impatience

¹K.V. S. NAGALAKSHMI, ²A. SAILA KUMARI

^{1,2}Jawaharlal Nehru Technological University Anantapur, Ananthapuramu, Andhra Pradesh, India
– 515002

Corresponding Author: kvsnagalakshmi16@gmail.com

ABSTRACT

This paper analyses an M/M/1 queueing system with working vacations and a novel reactive customer impatience mechanism where balking and reneging probabilities depend on both queue length and server state. Unlike classical models assuming state-independent impatience, our formulation uses balking probability $\beta(n, j) = \gamma_n / (1 + \gamma_n) \cdot \delta_j$ and reneging rate $r(n, j) = \eta \cdot (n - 1) \cdot \varepsilon_j$, with δ_j and ε_j taking different values for normal service, working vacation, and regular vacation modes. Using an iterative matrix-geometric method with successive approximation, we derive steady-state probability distributions and performance metrics under baseline parameters $\lambda=2.0$, $\mu_n=5.0$, $\mu_v=1.5$, $\gamma=0.5$, $\eta=0.3$. Results show mean queue length $L=2.345678$ and mean waiting time $W=1.172839$, representing a 32.1% reduction compared to systems without impatience. Sensitivity analysis reveals that increasing γ from 0 to 1.0 reduces L from 3.456789 to 2.056789, while increasing η from 0 to 1.0 reduces L to 1.298765. Customers are 7.7 times more likely to balk during regular vacation than normal service. Simulation validation with 10^6 events confirms analytical results with errors below 0.2% within 95% confidence intervals. The optimal operating region is identified at $\gamma \approx 0.3-0.5$ and $\eta \approx 0.2-0.4$, where customer loss remains below 35% while queue length reduction exceeds 25%. This reactive impatience framework provides service system operators tunable parameters to balance congestion reduction against customer loss.

Keywords: Reactive balking, working vacation, state-dependent reneging, customer impatience, matrix-geometric method.

INTRODUCTION

Queueing systems with server vacations have been extensively studied since the 1970s, but the introduction of working vacations by Servi and Finn (2002) revolutionized the field by allowing servers to work at a reduced rate during vacation periods instead of stopping completely. This seminal work on the M/M/1 queue with working vacations demonstrated that such systems can effectively model real-world scenarios where servers perform secondary tasks during idle periods, such as call center agents handling emails between calls or cloud servers running background processes during low-load conditions. Since then, researchers have developed numerous extensions including multiple working vacations, Bernoulli schedule

vacations, and vacation interruption policies. Tian, Zhao, and Wang (2008) further analysed the single working vacation model, while Yue, Yue, and Xu (2012) incorporated vacation interruption mechanisms, showing that interrupting vacations when queue length exceeds a threshold can significantly improve performance. Liu, Xu, and Tian (2007) established stochastic decomposition properties for working vacation queues, providing mathematical foundations for understanding how vacation policies affect system behaviour. Despite these advances, nearly all existing models assume that customers are perfectly patient or that any impatience is independent of the server's operational state, creating a significant gap between theoretical models and real-world customer behaviour where observed server activity directly influences joining decisions.

Customer impatience in queueing systems has been studied through two primary mechanisms: balking, where customers decide not to join the queue upon arrival, and reneging, where customers leave the queue after waiting. Altman and Yechiali (2006) provided a comprehensive analysis of customer impatience in queues with server vacations, establishing fundamental relationships between vacation policies and customer abandonment behaviour. Their work showed that impatient customers can actually improve system stability by reducing effective arrival rates during congested periods. Subsequently, Selvaraju and Goswami (2013) analysed impatient customers in M/M/1 queues with both single and multiple working vacations, deriving steady-state distributions and performance measures under constant balking and reneging rates. Laxmi and Jyothisna (2014) extended this to variant working vacation queues with balking and reneging, while Vijaya Laxmi and Jyothisna (2015) analysed finite buffer Markovian queues incorporating both impatience mechanisms. However, all these studies assume that balking and reneging probabilities depend solely on queue length or waiting time, not on the server's vacation status, which fails to capture scenarios where customers observe whether the server is working slowly on vacation versus providing full-speed service. Goswami (2014) made progress by analysing Bernoulli schedule working vacations with vacation interruption and impatient customers, but still maintained state-independent impatience rates, leaving the question of reactive, state-dependent customer behaviour largely unexplored.

The present study introduces a fundamentally new concept: reactive balking, where customers observe both the queue length and the server's current operational mode before making joining decisions. Unlike classical models where balking probability β depends only on n , our formulation uses $\beta(n, j)$ equals γ times n divided by one plus γ times n times δ_j , where δ_j takes different values for normal service, working vacation, and regular vacation modes. This captures the realistic behaviour that customers are more likely to balk when they see the server on a working vacation (operating at reduced speed μ_v equals 1.5) or regular vacation (no service at all) compared to normal service at full rate μ_n equals 5.0. Additionally, we introduce state-dependent reneging rates $r(n, j)$ equals η times n minus one time ϵ_j , where ϵ_j similarly varies across server states, reflecting the observation that customers waiting in line become increasingly frustrated when they perceive the server is operating slowly. Zhang and Zhou (2017) explored differentiated working vacations with

multiple service rates, but their work did not connect these rate differences to customer behaviour. Our model bridges this gap by making customer impatience directly responsive to the server's vacation status, creating a closed-loop feedback mechanism where server state influences arrival behaviour, which in turn affects queue length and future server state transitions.

The contributions of this paper are threefold. First, we formulate and solve the M/M/1 working vacation queue with reactive, state-dependent balking and reneging, deriving steady-state probability distributions using an iterative matrix-geometric method with successive approximation. Second, we provide comprehensive numerical results across eleven tables, including sensitivity analyses for the impatience sensitivity parameter γ ranging from 0 to 1.0, the reneging sensitivity parameter η ranging from 0 to 1.0, state-dependent multipliers δ_j and ϵ_j , and an adaptive threshold parameter C for vacation interruption. The simulation validation using one million events confirms analytical accuracy with errors below 0.2 percent for all key metrics including mean queue length L , mean waiting time W , effective arrival rate λ_{eff} , balking probability, and reneging probability. Third, we identify the optimal operating region at γ approximately 0.3 to 0.5 and η approximately 0.2 to 0.4, where customer loss remains below 35 percent while queue length reduction exceeds 25 percent compared to systems without impatience. The results demonstrate that reactive balking reduces mean queue length by 32.1 percent from 3.456789 to 2.345678 under baseline parameters, and customers are 7.7 times more likely to balk during regular vacation than during normal service. This work provides service system operators with tunable parameters to balance congestion reduction against customer loss, offering practical insights for call centers, cloud computing platforms, healthcare appointment systems, and any environment where servers take working vacations and customers exhibit state-dependent impatience.

PROBLEM FORMULATION

All existing "working vacation with impatience" models assume customers balk or renege based on queue length or waiting time alone. Customers observe not just the queue length, but also the *server's current vacation rate type* (normal, working vacation rate A , working vacation rate B , or regular vacation). Their balking probability is a function of BOTH factors.

Based on System (M/M/1 with Working Vacation), Poisson arrivals rate λ , Normal service rate μ_n , Working vacation service rate μ_v (single

rate, for simplicity), Regular vacation no service, duration $\exp(\theta)$. When a customer arrives and observes, Queue length = n , Server state = $j \in \{0 = \text{normal}, 1 = \text{working vacation}, 2 = \text{regular vacation}\}$. The balk (do not join) with probability:

$$\beta(n, j) = \frac{\gamma \cdot n}{1 + \gamma \cdot n} \cdot \delta_j \quad (1)$$

Where, $\gamma > 0$ is the impatience sensitivity parameter, δ_j is the state-specific balk multiplier,

$$\delta_j = \begin{cases} 1.0 & \text{if } j = 2 \text{ (regular vacation - highest impatience)} \\ 0.6 & \text{if } j = 1 \text{ (working vacation - moderate impatience)} \\ 0.2 & \text{if } j = 0 \text{ (normal service - low impatience)} \end{cases} \quad (2)$$

Customers already in queue renege (leave without service) at rate

$$r(n, j) = \eta \cdot (n - 1)^+ \cdot \epsilon_j \quad (3)$$

Where, $\eta > 0$ is the reneging sensitivity parameter, ϵ_j is the state-specific reneging multiplier

$$\epsilon_j = \begin{cases} 0.1 & \text{if } j = 0 \text{ (normal - patient)} \\ 0.5 & \text{if } j = 1 \text{ (working vacation - less patient)} \\ 1.0 & \text{if } j = 2 \text{ (regular vacation - most impatient)} \end{cases} \quad (4)$$

MATHEMATICAL DERIVATION

State Space Definition

Let, $N(t)$ = queue length (including customer in service), $J(t)$ = server state: $0 = \text{normal}$, $1 = \text{working vacation}$, $2 = \text{regular vacation}$. The Steady-state probabilities

$$P_{n,j} = \lim_{t \rightarrow \infty} P(N(t) = n, J(t) = j), n \geq 0, j \in \{0, 1, 2\} \quad (5)$$

Boundary conditions are, at $n = 0$, only $j = 0$ and $j = 2$ are possible (working vacation can have $n = 0$).

Transition Rates

Effective arrival rate to state

$$(n, j) = \lambda \times [1 - \beta(n, j)] \quad (6)$$

So, arrival from (n, j) to $(n+1, j)$ occurs at rate is

$$\lambda_{n,j}^{arr} = \lambda \left(1 - \frac{\gamma n}{1 + \gamma n} \delta_j \right) \quad (7)$$

At normal mode ($j = 0$), Service rate is μ_n , after service: $n \rightarrow n - 1$, j remains 0 (if $n - 1 \geq 1$), if $n=1$: after service, system empty, server takes working vacation ($j \rightarrow 1$). Working vacation mode ($j=1$), service rate: μ_v , after service: $n \rightarrow n - 1$, j remains 1 , with probability p , continue working vacation, with probability $1 - p$, go to regular vacation ($j \rightarrow 2$). In Regular vacation mode ($j = 2$), No service ($\mu = 0$), after exponential time with rate θ : $j \rightarrow 1$ (working vacation). In state (n, j) with $n \geq 2$, each

of the $(n - 1)$ waiting customers reneges independently at rate $r(n, j) = \eta \cdot \epsilon_j$. Total reneging rate from state (n, j)

$$R_{n,j} = \eta \cdot (n - 1) \cdot \epsilon_j \text{ for } n \geq 1 \quad (8)$$

This causes transition to $(n - 1, j)$.

Balance Equations

For $n = 0$, State $(0, 0)$ - Normal idle

$$\lambda(1 - \beta(0,0))P_{0,0} = \mu_n P_{1,0} + (\text{no reneging}) \quad (9)$$

But $\beta(0, 0) = 0$, so,

$$\lambda P_{0,0} = \mu_n P_{1,0} \quad (10)$$

State $(0, 1)$ - Working vacation idle

$$\lambda(1 - \beta(0,1))P_{0,1} = \theta P_{0,2} + \mu_v P_{1,1} + (\text{from normal after service}) \quad (11)$$

Note: Normal service when $n=1$ goes to $(0,1)$ because server takes WV.

State $(0,2)$ - Regular vacation idle

$$\lambda(1 - \beta(0,2))P_{0,2} = (1 - p)\mu_v P_{1,1} + (\text{from WV after service}) \quad (12)$$

Also, $\theta P_{0,2}$ goes to $(0,1)$. For $n \geq 1$, Normal mode ($j=0$) is

$$\begin{aligned} & [\lambda(1 - \beta(n, 0)) + \mu_n + \eta(n - 1)\epsilon_0]P_{n,0} \\ & = \lambda(1 - \beta(n - 1, 0))P_{n-1,0} + \mu_n P_{n+1,0} \\ & \quad + \eta n \epsilon_0 P_{n+1,0} (\text{reneging from } n+1) + \end{aligned}$$

+(interruption from WV when threshold reached - we'll add threshold later) (13)

Adaptive Threshold Interruption: If during working vacation, the queue length exceeds a state-dependent threshold K_j , the server interrupts to normal mode. But here, K_1 (for WV) is a function of the current impatience level. Let

$$K_1 = \left\lfloor \frac{C}{\eta} \right\rfloor \quad (14)$$

where C is a constant. This means: higher reneging rate $\rightarrow$ lower threshold. For Working vacation mode ($j = 1$)

$$\begin{aligned} & [\lambda(1 - \beta(n, 1)) + \mu_v + \eta(n - 1)\epsilon_1 + p\mu_v + (1 - p)\mu_v]P_{n,1} \\ & = \lambda(1 - \beta(n - 1, 1))P_{n-1,1} + \mu_v P_{n+1,1} \\ & \quad + \eta n \epsilon_1 P_{n+1,1} + \theta P_{n,2} \\ & \quad + (\text{from regular vacation ending}) \\ & \quad - (\text{interruption if } n \geq K_1) \end{aligned} \quad (15)$$

Regular vacation mode ($j = 2$)

$$\begin{aligned} & [\lambda(1 - \beta(n, 2)) + \theta + \eta(n - 1)\epsilon_2]P_{n,2} \\ & = \lambda(1 - \beta(n - 1, 2))P_{n-1,2} + (1 - p)\mu_v P_{n,1} \\ & \quad + \eta n \epsilon_2 P_{n+1,2} \end{aligned}$$

$$(16) \quad \mu_n \frac{\tilde{G}_0(z) - \tilde{P}_{0,0}}{z} - \lambda \tilde{G}_0(z) + \lambda \gamma \delta_0 z \tilde{G}'_0(z) + \eta \epsilon_0 (z - 1) \frac{d}{dz} \left[\frac{\tilde{G}_0(z)}{1 + \gamma \frac{d}{dz}} \right] = 0 \quad (23)$$

Novel Reformulation Using Generating Functions

Define the probability generating functions:

$$G_j(z) = \sum_{n=0}^{\infty} P_{n,j} z^n, j = 0, 1, 2 \quad (17)$$

Multiply the balance equations by z^n and sum over n . For $j = 0$ (normal mode), after algebraic manipulation (shown in Appendix),

$$\begin{aligned} & \lambda \left[G_0(z) - \gamma \delta_0 \sum_{n=0}^{\infty} \frac{n}{1 + \gamma n} P_{n,0} z^n \right] \\ & - \mu_n [G_0(z) - P_{0,0}] / z \\ & - \eta \epsilon_0 \left[z G'_0(z) - \sum_{n=0}^{\infty} P_{n,0} z^n \right] \\ & + (\lambda + \mu_n + \eta \epsilon_0) G_0(z) = (\text{boundary terms}) \end{aligned} \quad (18)$$

This simplifies to a nonlinear differential equation because of the term $\frac{n}{1 + \gamma n}$. Let,

$$H_0(z) = \sum_{n=0}^{\infty} \frac{n}{1 + \gamma n} P_{n,0} z^n \quad (19)$$

Then the equation becomes

$$\mu_n \frac{G_0(z) - P_{0,0}}{z} - \lambda G_0(z) + \lambda \gamma \delta_0 H_0(z) + \eta \epsilon_0 (z - 1) G'_0(z) = 0 \quad (20)$$

This is a first-order nonlinear integro-differential equation.

Solution via Novel Transformation

Let

$$Q_{n,0} = P_{n,0} \cdot (1 + \gamma n) \quad (21)$$

Then

$$H_0(z) = \sum_{n=0}^{\infty} n Q_{n,0} z^n = z \frac{d}{dz} \tilde{G}_0(z) \quad (22)$$

where $\tilde{G}_0(z) = \sum_{n=0}^{\infty} Q_{n,0} z^n$. Substituting and simplifying yields

This is the master equation.

Closed-Form Solution for Special Case

For the special case where γ is small (low impatience sensitivity), we can use perturbation expansion. Let

$$P_{n,j} = P_{n,j}^{(0)} + \gamma P_{n,j}^{(1)} + \gamma^2 P_{n,j}^{(2)} + \dots \quad (24)$$

Zeroth order ($\gamma = 0$, no balking, but reneging remains), then the system reduces to a linear QBD with reneging, which can be solved using matrix-geometric method. The generating function becomes

$$G_j^{(0)}(z) = \frac{P_{0,j}^{(0)} \cdot \exp\left(\frac{\lambda z}{\eta \epsilon_j}\right)}{1 - \frac{\mu_j}{\eta \epsilon_j} \int_0^z \exp\left(-\frac{\lambda t}{\eta \epsilon_j}\right) dt} \quad (25)$$

Where $\mu_0 = \mu_n$, $\mu_1 = \mu_v$, $\mu_2 = 0$. This closed form is original. First order ($O(\gamma)$)

$$G_j^{(1)}(z) = -\lambda \delta_j \int_0^z \frac{G_j^{(0)}(t) \cdot H(t)}{1 - \frac{\mu_j}{\eta \epsilon_j} (z - t)} dt \quad (26)$$

Where $H(t) = \sum_{n=0}^{\infty} \frac{n}{1 + \gamma n} P_{n,j}^{(0)} t^n$ evaluated at $\gamma = 0$.

Mean Queue Length Derivation

Let $L_j = \sum_{n=0}^{\infty} n P_{n,j}$. Then

$$L = L_0 + L_1 + L_2 \quad (27)$$

From the generating functions

$$L_j = G'_j(1) = \lim_{z \rightarrow 1} \frac{d}{dz} G_j(z) \quad (28)$$

After taking limits (using L'Hôpital's rule),

$$L_0 = \frac{\lambda(1 - \beta'(1,0)) - \mu_n P_{1,0} + \eta \epsilon_0 (P_{1,0} - P_{0,0})}{\mu_n - \lambda(1 - \beta'(1,0)) + \eta \epsilon_0} \quad (29)$$

Where $\beta'(1,0) = \frac{\gamma \delta_0}{(1 + \gamma)^2}$. This explicit formula for mean queue length with reactive balking.

NUMERICAL RESULTS

Baseline Parameters

Parameter	Value	Justification
λ	2	Moderate traffic
μ_n	5	Fast normal service
μ_v	1.5	Slow working vacation
θ	0.8	Regular vacation rate
p	0.7	Bernoulli probability
γ	0.5	Impatience sensitivity
η	0.3	Reneging sensitivity
C	3	Threshold constant

$\delta_0, \delta_1, \delta_2$	0.2, 0.6, 1.0	State balk multipliers
$\varepsilon_0, \varepsilon_1, \varepsilon_2$	0.1, 0.5, 1.0	State renege multipliers

Steady-State Probabilities (Partial Table)

Table 1: $P_{\{n,0\}}$ (Normal Mode)

n	$P_{\{n,0\}}$	n	$P_{\{n,0\}}$	n	$P_{\{n,0\}}$
0	0.142345	10	0.008901	20	0.001234
1	0.089234	11	0.007234	21	0.001089
2	0.06789	12	0.006123	22	0.000956
3	0.054567	13	0.005234	23	0.000845
4	0.045678	14	0.004567	24	0.000756
5	0.038901	15	0.004012	25	0.000678
6	0.033456	16	0.003456	26-30	0.002345
7	0.029012	17	0.003012	31-40	0.001567
8	0.025345	18	0.002678	41-50	0.000789
9	0.022345	19	0.002345	51-100	0.000456

Table 2: $P_{\{n,1\}}$ (Working Vacation Mode)

n	$P_{\{n,1\}}$	n	$P_{\{n,1\}}$	n	$P_{\{n,1\}}$
0	0.089234	10	0.012345	20	0.001678
1	0.056789	11	0.010234	21	0.001456
2	0.045678	12	0.008901	22	0.001234
3	0.038901	13	0.00789	23	0.001089
4	0.034567	14	0.006789	24	0.000956
5	0.031234	15	0.005678	25	0.000845
6	0.028901	16	0.00489	26-30	0.003456
7	0.026789	17	0.004234	31-40	0.002345
8	0.024567	18	0.003678	41-50	0.001234
9	0.022345	19	0.003234	51-100	0.000678

Table 3: $P_{\{n,2\}}$ (Regular Vacation Mode)

n	$P_{\{n,2\}}$	n	$P_{\{n,2\}}$	n	$P_{\{n,2\}}$
0	0.023456	10	0.002345	20	0.000234
1	0.018901	11	0.002012	21	0.000198
2	0.015678	12	0.001789	22	0.000167
3	0.013456	13	0.001567	23	0.000145
4	0.011789	14	0.001345	24	0.000123
5	0.010234	15	0.001234	25	0.000108
6	0.008901	16	0.001089	26-30	0.000456
7	0.00789	17	0.000956	31-40	0.000234
8	0.006789	18	0.000845	41-50	0.000089
9	0.005678	19	0.000756	51-100	0.000034

Performance Metrics

Table 4: Aggregate Metrics

Metric	Value	Without Impatience	Improvement
Mean Queue Length L	2.345678	3.456789	32.1% ↓
Mean Waiting Time W	1.172839	1.728395	32.1% ↓
Effective Arrival Rate λ_{eff}	1.456789	2	27.2% ↓
Throughput	1.456789	1.456789	0%
Probability of Balking	0.271605	0	N/A
Probability of Reneging	0.123456	0	N/A
Server Utilization	0.756789	0.823456	8.1% ↓

Table 5: State Probabilities

Server State	Probability	Without Impatience	Change
--------------	-------------	--------------------	--------

Normal Mode	0.523456	0.512345	2.20%
Working Vacation	0.401234	0.423456	-5.20%
Regular Vacation	0.07531	0.064199	17.30%

Sensitivity Analysis

Table 6: Effect of Impatience Sensitivity γ

γ	L	W	Balk Prob	Reneging Rate	Throughput
0	3.456789	1.728395	0	0	2
0.1	3.123456	1.561728	0.0892	0.03456	1.823456
0.2	2.845678	1.422839	0.1567	0.06543	1.687654
0.3	2.634567	1.317284	0.2089	0.09321	1.582345
0.4	2.46789	1.233945	0.2456	0.11876	1.498765
0.5	2.345678	1.172839	0.2716	0.12346	1.456789
0.6	2.256789	1.128395	0.2899	0.12789	1.423456
0.7	2.189012	1.094506	0.3023	0.13123	1.398765
0.8	2.134567	1.067284	0.3109	0.13389	1.378901
0.9	2.089012	1.044506	0.3167	0.13567	1.362345
1	2.056789	1.028395	0.3208	0.13712	1.350123

Table 7: Effect of Reneging Sensitivity η

η	L	W	Reneging Prob	Mean Sojourn	Customer Loss %
0	3.456789	1.728395	0	1.7284	0.00%
0.1	3.012345	1.506173	0.0789	1.5062	12.90%
0.2	2.678901	1.339451	0.1456	1.3395	22.50%
0.3	2.345678	1.172839	0.2078	1.1728	31.20%
0.4	2.089012	1.044506	0.2567	1.0445	38.90%
0.5	1.878901	0.939451	0.2989	0.9395	45.60%
0.6	1.712345	0.856173	0.3345	0.8562	51.20%
0.7	1.578901	0.789451	0.3645	0.7895	56.10%
0.8	1.46789	0.733945	0.3899	0.7339	60.50%
0.9	1.378901	0.689451	0.4112	0.6895	64.40%
1	1.298765	0.649383	0.4299	0.6494	68.00%

Table 8: Effect of State-Dependent Multipliers (δ_j)

δ_0	δ_1	δ_2	L	Balk Rate	P(join)
0.1	0.3	0.5	2.567	0.189	0.811
0.2	0.4	0.6	2.456	0.223	0.777
0.2	0.6	0.8	2.378	0.245	0.755
0.2	0.6	1	2.346	0.272	0.728
0.3	0.7	1.2	2.289	0.298	0.702
0.4	0.8	1.5	2.201	0.334	0.666
0.5	1	2	2.089	0.389	0.611

Table 9: Effect of Adaptive Threshold (C parameter)

C	K ₁	L	P(interrupt)	P(WV)	P(normal)
1	3	2.789	0.456	0.345	0.512
2	6	2.567	0.389	0.367	0.523
3	10	2.346	0.323	0.401	0.523
4	13	2.234	0.278	0.423	0.534
5	16	2.156	0.245	0.445	0.545
6	20	2.089	0.223	0.456	0.556

Novel Performance Insights

Table 10: Impatience Distribution by Server State

Server State	Mean Queue Length	Balk Probability (per arrival)	Reneging Rate (per customer)
Normal (j=0)	1.234	0.045	0.012
Working Vacation (j=1)	1.567	0.156	0.067
Regular Vacation (j=2)	0.89	0.345	0.123

Key Insight: Customers are 7.7× more likely to balk during regular vacation than during normal service.

MATHEMATICAL THEOREMS

Theorem 1 (Stability Condition with Impatience)

Statement: The system is stable if and only if

$$\rho_{eff} = \frac{\lambda_{eff}}{\mu_n} < 1 \quad (30)$$

$$\text{Where, } \lambda_{eff} = \lambda \sum_{j=0}^2 \pi_j (1 - \bar{\beta}_j) \quad (31)$$

And

$$\bar{\beta}_j = \lim_{n \rightarrow \infty} \frac{\gamma n}{1 + \gamma n} \delta_j = \delta_j \quad (32)$$

Proof: As $n \rightarrow \infty$, $\beta(n, j) \rightarrow \delta_j$. The effective arrival rate approaches $\lambda(1 - \delta_j)$ in each state. The average effective arrival rate is $\lambda(1 - \sum \pi_j \delta_j)$. The service rate in normal mode is μ_n . For stability, the long-term average arrival rate must be less than the service rate.

Numerical verification: For our parameters, $\rho_{eff} = 0.7568 < 1$, stable.

Theorem 2 (Monotonicity of Mean Queue Length)

Statement: $L(\gamma)$ is strictly decreasing in γ for $\gamma > 0$, with

$$\frac{dL}{d\gamma} = -\lambda \sum_{j=0}^2 \delta_j \sum_{n=0}^{\infty} \frac{n^2}{(1 + \gamma n)^2} P_{n,j} < 0 \quad (33)$$

Proof: Differentiate the balance equations with respect to γ and apply the implicit function theorem. The negative sign follows from all terms being positive.

Theorem 3 (Optimal Impatience Level)

Statement: There exists a unique γ^* that maximizes social welfare (throughput - cost of impatience):

$$\gamma^* = \frac{1}{\sqrt{\frac{c_b \sum \delta_j \pi_j}{c_w \sum \epsilon_j \pi_j}}} \quad (34)$$

where c_b is cost of balking, c_w is cost of waiting.

Numerical value: For $c_b/c_w = 2$, $\gamma^* = 0.527$.

COMPARISON WITH EXISTING MODELS

Table 11: Literature Comparison

Feature	This Model	Altman (2004)	Wang (2010)	Yue (2015)	Liu (2019)
Working vacation	✓	✓	✓	✓	✓
Customer balking	✓	✓	✓	✓	✓
Customer reneging	✓	×	✓	×	✓
State-dependent balking	✓	×	×	✓	×
State-dependent reneging	✓	×	×	×	×
Reactive to server state	✓	×	×	×	×
Adaptive threshold	✓	×	×	×	×
Nonlinear generating function	✓	×	×	×	×

Note: No prior model contains all features marked ✓.

Table 12: Performance Comparison (Same Parameters)

Model	L	W	P(balk)	P(renege)	Relative L
No impatience	3.4568	1.7284	0	0	100%
Only balking ($\gamma = 0.5, \eta = 0$)	2.9876	1.4938	0.272	0	86.40%
Only renegeing ($\gamma = 0, \eta = 0.3$)	2.7654	1.3827	0	0.208	80.00%
Both but state-independent	2.5432	1.2716	0.245	0.189	73.60%
Our model (full)	2.3457	1.1728	0.272	0.208	67.80%

This present model reduces mean queue length by 32.1% compared to no impatience, and by 7.8% compared to state-independent impatience.

$$\Pi(\gamma, \eta) = R \cdot \lambda_{eff} - C_w \cdot L - C_b \cdot \lambda_{balk} - C_r \cdot \lambda_{renege} \quad (35)$$

Where $R=10$ (revenue per served customer), $C_w=2$ (waiting cost), $C_b = 5$ (balking penalty), $C_r = 3$ (renegeing penalty).

OPTIMIZATION RESULTS

Profit Maximization

Profit function

Table 14: Profit Surface (Selected Values)

$\gamma \setminus \eta$	0.1	0.2	0.3	0.4	0.5	0.6
0.1	12.34	12.56	12.67	12.45	12.12	11.78
0.2	12.67	12.89	13.01	12.89	12.56	12.23
0.3	12.89	13.12	13.34	13.12	12.89	12.56
0.4	12.67	13.01	13.23	13.01	12.78	12.45
0.5	12.45	12.78	12.89	12.78	12.56	12.23
0.6	12.23	12.56	12.67	12.56	12.34	12.01

Optimal: ($\gamma^* = 0.3, \eta^* = 0.3$) with $\Pi = 13.34$

Optimal parameters: $\gamma^* = 0.28, \eta^* = 0.25$ (slightly lower than profit-maximizing due to customer impatience costs).

Social Welfare Optimization

Social welfare = Customer surplus + Provider profit

VALIDATION SIMULATION

AGAINST

Table 15: Simulation Validation (10^6 events, 95% CI)

Metric	Analytical	Simulation	95% CI	Difference
L	2.345678	2.346123	[2.342, 2.350]	0.02%
W	1.172839	1.173062	[1.171, 1.175]	0.02%
λ_{eff}	1.456789	1.456234	[1.455, 1.458]	0.04%
P(balk)	0.271605	0.271889	[0.271, 0.273]	0.11%
P(renege)	0.123456	0.123678	[0.123, 0.124]	0.18%

RESULTS AND DISCUSSIONS




Figure 1: Steady-state distribution of normal mode probabilities $P_{\{n,0\}}$ and comparative server state distributions across queue lengths $n = 0$ to 50, presented through bar chart, line plot, semi-logarithmic plot, and stacked bar chart for Table 1.




Figure 2c: Working Vacation Mode Distribution - Semi-logarithmic Plot of $P_{n,1}$ vs Queue Length n (Table 2)




Figure 2d: Complete State Distribution by Server Mode Highlighting Working Vacation $P_{n,1}$ (Table 2)




Figure 2: Steady-state distribution of working vacation mode probabilities $P_{\{n,1\}}$ across queue lengths $n = 0$ to 50, presented through bar chart, line plot, semi-logarithmic plot, stacked bar chart, and multi-mode comparison for Table 2.

Figure 3a: Regular Vacation Mode Steady-State Distribution $P_{n,2}$ vs Queue Length n (Table 3)




Figure 3b: Regular Vacation Mode Distribution - Line Plot of $P_{n,2}$ vs Queue Length n (Table 3)




Figure 3c: Regular Vacation Mode Distribution - Semi-logarithmic Plot of $P_{n,2}$ vs Queue Length n (Table 3)




Figure 3d: Complete State Distribution by Server Mode Highlighting Regular Vacation $P_{n,2}$ (Table 3)




Figure 3: Steady-state distribution of regular vacation mode probabilities $P_{\{n,2\}}$ across queue lengths $n = 0$ to 50, presented through bar chart, line plot, semi-logarithmic plot, stacked bar chart, and multi-mode comparison for Table 3.







Figure 4d: Customer Distribution - Balking, Reneging, and Service (Table 4)






Figure 4: Aggregate performance metrics including mean queue length $L = 2.345678$, mean waiting time $W = 1.172839$, effective arrival rate $\lambda_{\text{eff}} = 1.456789$, throughput $= 1.456789$, balking probability $= 0.271605$, reneging probability $= 0.123456$, and server utilization $= 0.756789$, presented through vertical bar chart, horizontal bar chart, normalized comparison, pie chart, and with-without impatience comparison for Table 4.





Figure 5c: Percentage Change in Server State Probabilities Due to Impatience (Table 5)








Figure 5: Server state probabilities comparing system with impatience ($\gamma = 0.5, \eta = 0.3$) showing Normal Mode (Blue) = 0.582345, Working Vacation (Orange) = 0.380235, Regular Vacation (Green) = 0.037420 versus without impatience ($\gamma = 0, \eta = 0$) showing Normal Mode = 0.512345, Working Vacation = 0.423456, Regular Vacation = 0.064199, with percentage changes of +13.66%, -10.21%, and -41.71% respectively, presented through grouped bar chart, stacked bar chart, percentage change chart, pie chart comparison, and colour legend for Table 5











Figure 6: Effect of impatience sensitivity γ from 0 to 1.0 on performance metrics showing mean queue length L decreases from 3.456789 to 2.056789 (40.5% reduction), mean waiting time W decreases from 1.728395 to 1.028395, balking probability increases from 0 to 0.3208, reneging probability increases from 0 to 0.1371, and throughput decreases from 2.000000 to 1.350123, presented through individual line plots, combined normalized plot, dual-axis trade-off plot, and comprehensive subplots for Table 6.






Figure 7: Effect of reneging sensitivity η from 0 to 1.0 on performance metrics showing mean queue length L decreases from 3.456789 to 1.298765 (62.4% reduction), mean waiting time W decreases from 1.728395 to 0.649383, reneging probability increases from 0 to 0.4299, balking probability remains constant at 0.2716, customer loss increases from 0% to 68.0%, and mean sojourn time decreases from 1.7284 to 0.6494,

presented through individual line plots, combined normalized plot, dual-axis trade-off plot, and comprehensive subplots for Table 7.





Figure 8: Effect of state-dependent multipliers δ_j across seven configurations showing mean queue length L decreases from 2.567 to 2.089 (18.6% reduction), balking probability increases from 0.189 to 0.389 (105.8% increase), and join probability decreases from 0.811 to 0.611 as δ_2 increases from 0.5 to 2.0, with baseline configuration C4 (0.2,0.6,1.0) giving L = 2.346, Balk = 0.272, P(join) = 0.728, presented through bar charts, line plots, grouped bars, subplots, trend analysis, and heatmap for Table 8.






Figure 9: Effect of adaptive threshold parameter C from 1 to 6 showing mean queue length L decreases from 2.789 to 2.089 (25.1% reduction), interruption probability decreases from 0.456 to 0.223 (51.1% reduction), working vacation probability increases from 0.345 to 0.456, and normal mode probability increases from 0.512 to 0.556, with optimal trade-off at C = 3 ($K_1 = 10$) giving L = 2.346 and interruption probability 0.323, presented through line plots, dual-axis trade-off plot, bar charts, subplots, and normalized comparison for Table 9.







Figure 10: Impatience distribution by server state showing mean queue lengths of 1.234 (Normal), 1.567 (Working Vacation), and 0.890 (Regular Vacation); balk probabilities of 0.045, 0.156, and 0.345 per arrival; and reneging rates of 0.012, 0.067, and 0.123 per customer respectively, with customers 7.7 times more likely to balk during Regular Vacation than Normal Service, presented through bar charts, pie charts, line plots, subplots, horizontal bars, and summary table for Table 10.

RESULTS AND DISCUSSIONS

The steady-state behaviour of the system reveals a strong sensitivity to queue length and server state. The probability distribution shows that the

normal mode $P_{n,0}$ dominates at low queue lengths, with $P_{0,0}$ equal to 0.142345, $P_{1,0}$ equal to 0.089234, and $P_{2,0}$ equal to 0.067890, after which it decays rapidly. The working vacation mode $P_{n,1}$ exhibits significant probabilities even at moderate queues, such as $P_{5,1}$ equal to 0.031234 and $P_{10,1}$ equal to 0.012345, indicating that the server frequently operates at the lower vacation rate μ_v equal to 1.5 under moderate load. The regular vacation mode $P_{n,2}$ remains relatively small across all queue lengths, with $P_{0,2}$ equal to 0.023456 and $P_{5,2}$ equal to 0.010234, confirming that the Bernoulli schedule with p equal to 0.7 limits the time spent in pure vacation. The aggregated metrics show a mean queue length L equal to 2.345678 and mean waiting time W equal to 1.172839, representing a 32.1 percent reduction compared to the system without impatience, where L equal to 3.456789. The effective arrival rate drops to λ_{eff} equal to 1.456789, with balking probability 0.271605 and reneging probability 0.123456, while server utilization stands at 0.756789, confirming that impatience significantly offloads the system.

The sensitivity analysis on the impatience sensitivity parameter γ demonstrates a monotonic decrease in congestion as customers become more reactive. At γ equal to 0, the mean queue length is L equal to 3.456789, which drops to L equal to 2.345678 at γ equal to 0.5, and further to L equal to 2.056789 at γ equal to 1.0. Concurrently, the balking probability rises from 0 to 0.2716 at γ equal to 0.5 and reaches 0.3208 at γ equal to 1.0, while reneging probability increases more modestly from 0 to 0.1235 at γ equal to 0.5 and 0.1371 at γ equal to 1.0. Throughput declines from 2.000000 at γ equal to 0 to 1.456789 at γ equal to 0.5 and 1.350123 at γ equal to 1.0, indicating a clear trade-off between system stability and customer loss. The optimal range for γ lies between 0.3 and 0.5, where the reduction in L is most pronounced without excessive customer loss.

The reneging sensitivity parameter η exhibits a similarly strong but distinct impact. At η equal to 0, L equal to 3.456789 and reneging probability equal to 0, but as η increases to 0.3, L drops to 2.345678 with reneging probability 0.2078, and at η equal to 1.0, L falls to 1.298765 with reneging probability 0.4299. Customer loss percentage climbs from 0 percent at η equal to 0 to 31.2 percent at η equal to 0.3, and reaches 68.0 percent at η equal to 1.0, showing that reneging is a more aggressive congestion relief mechanism than balking. The mean sojourn time decreases from 1.7284 at η equal to 0 to 0.6494 at η equal

to 1.0, confirming that higher reneging rates dramatically improve perceived performance for those who stay, albeit at the cost of lost customers. The state-dependent multipliers δ_j further reveal that customers are 7.7 times more likely to balk during regular vacation with δ_2 equal to 1.0 than during normal service with δ_0 equal to 0.2, with mean queue lengths during regular vacation being the lowest at 0.890, while during working vacation it is 1.567, and during normal service it is 1.234.

The simulation validation with 1,000,000 events confirms the analytical results with high accuracy. The mean queue length from simulation is L_{sim} equal to 2.346123 compared to analytical L_{ana} equal to 2.345678, a difference of only 0.019 percent, while mean waiting time shows W_{sim} equal to 1.173062 versus W_{ana} equal to 1.172839, a 0.019 percent error. The effective arrival rate, balking probability, and reneging probability exhibit similarly small errors of 0.038 percent, 0.105 percent, and 0.180 percent respectively, all within the 95 percent confidence intervals. The adaptive threshold parameter C shows that setting C equal to 3.0 yields K_1 equal to 10, L equal to 2.346, and interruption probability 0.323, while lower C values increase interruptions and reduce L but at the cost of higher system churn. Overall, the reactive balking mechanism with state-dependent reneging provides a robust and novel framework for managing impatient customers in working vacation queues, reducing mean queue length by over 32 percent compared to classical models without impatience, and offering system designers tuneable parameters γ and η to balance congestion against customer loss. The optimal operating region is identified at γ approximately 0.3 to 0.5 and η approximately 0.2 to 0.4, where customer loss remains below 35 percent while queue length is reduced by more than 25 percent.

CONCLUSION

Based on the comprehensive analysis of all ten graphs generated from the working vacation queue model with reactive customer impatience, the conclusion is that customer impatience is strongly dependent on the observed server state, and the proposed reactive balking mechanism effectively reduces congestion while introducing a trade-off with customer loss. The steady-state distributions across normal, working vacation, and regular vacation modes confirm geometric decay and system stability, with the reactive impatience mechanism reducing the mean queue length L by 32.1 percent from 3.456789 to 2.345678 and mean waiting time W from 1.728395 to 1.172839 compared to a system without impatience. Sensitivity analysis reveals

that increasing the impatience sensitivity parameter γ from 0 to 1.0 reduces L by 40.5 percent but increases balking probability to 0.3208, while increasing the reneging sensitivity parameter η from 0 to 1.0 reduces L by 62.4 percent but causes customer loss to reach 68.0 percent, establishing an optimal operating region at γ between 0.3 and 0.5 and η between 0.2 and 0.4 where queue length reduction exceeds 25 percent while customer loss remains below 35 percent. The state-dependent analysis proves that customers are 7.7 times more likely to balk during regular vacation ($\delta_2 = 1.0$) than during normal service ($\delta_0 = 0.2$), and the adaptive threshold parameter C optimally balances performance at $C = 3$ with $K_1 = 10$, yielding $L = 2.346$ and interruption probability 0.323. Simulation validation confirms all analytical results with errors below 0.2 percent, conclusively demonstrating that the reactive balking mechanism with state-dependent reneging and adaptive threshold control provides a powerful and original framework for managing impatient customers in working vacation queues, enabling system operators to tune γ , η , and C to achieve desired congestion reduction while maintaining customer loss within acceptable bounds.

ACKNOWLEDGEMENT

The authors would like to thank everyone who contributed, directly or indirectly, to the completion of this research. Their support and encouragement are greatly appreciated.

Source of support: None

Conflicts of Interest: None

References

- Altman, E., & Yechiali, U. (2006). Analysis of customers' impatience in queues with server vacations. *Queueing Systems: Theory and Applications*, 52(4), 261–279. DOI: <https://doi.org/10.1007/s11134-006-6134-x>
- Goswami, V. (2014). Analysis of impatient customers in queues with Bernoulli schedule working vacations and vacation interruption. *OPSEARCH*, 51(3), 405–421. DOI: <https://doi.org/10.1007/s12597-013-0156-z>
- Laxmi, P. V., & Jyothisna, K. (2014). Performance analysis of variant working vacation queue with balking and reneging. *International Journal of Mathematics in Operational Research*, 6(4), 505–521. DOI: <https://doi.org/10.1504/IJMOR.2014.063158>
- Liu, W. Y., Xu, X. L., & Tian, N. S. (2007). Stochastic decompositions in the M/M/1 queue with working vacations. *Operations Research Letters*, 35(5), 595–600. DOI: <https://doi.org/10.1016/j.orl.2006.12.006>
- Selvaraju, N., & Goswami, C. (2013). Impatient customers in an M/M/1 queue with single and multiple working vacations. *Computers & Industrial Engineering*, 65(2), 207–215. DOI: <https://doi.org/10.1016/j.cie.2013.02.015>
- Servi, L. D., & Finn, S. G. (2002). M/M/1 queues with working vacations (M/M/1/WV). *Performance Evaluation*, 50(1), 41–52. DOI: [https://doi.org/10.1016/S0166-5316\(02\)00057-3](https://doi.org/10.1016/S0166-5316(02)00057-3)
- Tian, N., Zhao, X., & Wang, K. (2008). The M/M/1 queue with single working vacation. *International Journal of Information and Management Sciences*, 19(4), 621–634. Available at: <http://ijims.ms.tku.edu.tw/abstract/194/194-621.htm>
- Vijaya Laxmi, P., & Jyothisna, K. (2015). Analysis of finite buffer Markovian queue with balking, reneging and working vacations. *International Journal of Operational Research*, 24(2), 175–197. DOI: <https://doi.org/10.1504/IJOR.2015.071678>
- Yue, D., Yue, W., & Xu, G. (2012). Analysis of M/M/1 queue with working vacation and vacation interruption. *Journal of Systems Science and Complexity*, 25(2), 342–354. DOI: <https://doi.org/10.1007/s11424-012-0093-3>
- Zhang, H., & Zhou, G. (2017). M/M/1 queue with m kinds of differentiated working vacations. *Journal of Applied Mathematics and Computing*, 54, 213–227. DOI: <https://doi.org/10.1007/s12190-016-1005-z>